stone tile

SPECIFICATION SHEET: KAFÉ KLIC SERIES

PLANK FORMAT:	METRIC:	IMPERIAL:	
STRUCTURE:	ENGINEERED	ENGINEERED	
PROFILE:	CLIC	CLIC	
WIDTH:	125MM	5"	
LENGTH:	400-1900MM	15.75" TO 75" RL	(Approx 50% full 1900mm length boards)
THICKNESS:	14MM	9/16"	

BOX & PALLET INFO:	METRIC:	IMPERIAL:
SF / M2 / BOX:	2.85 M2	30.68 SF
SF / PALLET:	102.6 M2	1104.48 SF
BOXES / PALLET:	36	36
BOX DIMENSIONS:	1930 L X 268 W X 95MM H	76" L X 10.5" W X 3.75" H
PALLET DIMENSIONS:	1930 L X 1075 W X 935MM H	76" L X 42.25" W X 37" H
BOX WEIGHT:	26 KG	57.5 LBS
PALLET WEIGHT:	956 KG	2100 LBS
PALLET BOX PACKING:	4 WIDE X 9 HIGH	4 WIDE X 9 HIGH

CONTAINER LOADING INFO:	METRIC:	IMPERIAL:
SF/M2 / 40' CONTAINER:	2770.2 M2	29,820.96 SF
BOXES / 40' CONTAINER:	972	972
PALLETS / 40' CONTAINER:	27	27

GENERAL PRODUCT INFORMATION:	
VENEER SPECIES:	WHITE OAK (QUERCUS ROBUR)
VENEER ORIGIN:	EUROPE
VENEER THICKNESS & TYPE:	2MM SLICED
MILLING PROFILE:	CLIC
SURFACE:	BRUSHED
BEVEL:	1 MM X 1 MM
COLOUR:	NATURAL (NO STAIN) MATCH ORIGINAL SAMPLE #8 (SAME AS SKU # 53002)
FINISH:	UV URETHANE (RESIDENTIAL GRADE)
GLOSS:	DURALOX® SUPERMATT 4° LOW GLOSS
GRADE:	ABCD
CHARACTER:	KNOTS, REPAIRS, FILLER, STRONG GRAIN VARIATIONS
CORE SPECIES:	EUCALYPTUS
GLUE:	CARB-2 CERTIFIED
WARRANTY:	35 YEAR LIMITED RESIDENTIAL

GENERAL INSTALLATION INFORMATION:

INSTALLATION: Clic-floating or glue-down (refer to installation guide for additional information and requirements)

NOTE: All dimensional and weight information noted herein is nominal.