

KYUSHU SIZE

MATERIALE MONOPOROSA IN PASTA BIANCA

MATERIAL WHITE BODY SINGLE FIRED WALL TILE

BORDO IRREGOLARE

EDGE IRREGULAR

FINITURA SUPERFICIE LUCIDA E MATT

FINISH GLOSSY AND MATT SURFACES

SPESSORE - THICKNESS 8,0 MM

V0 ASPETTO UNIFORME - UNIFORM ASPECT



5x25 / 2"x10" MATTE 169



5x25 / 2"x10" LUX 169



5441 - BIANCO



5454 - BIANCO



5447 - VERDE



5463 - VERDE



5442 - GRIGIO



5461 - GRIGIO



5453 - NERO



5465 - NERO

WALL

IMBALLI - PACKING

Formato cm	Pcs.	M ² /box	Kg/box	Box/pal.	M ² /pal.	Kg/pal.
5x25	24	0,276	4,00	150	41,40	600,00

KYUSHU TECHNICAL FEATURES



NORMA STANDARD	CARATTERISTICHE FEATURES	VALORE PRESCRITTO VALUE REQUIRED	KYUSHU
ISO 10545/2	DIMENSIONI - SIZE		
	lunghezza e larghezza length and width	± 0,5 %	± 0,5 %
	spessore thickness	± 10 %	± 10 %
	rettilineità degli spigoli straightness of edges	± 0,3 %	± 0,3 %
	ortogonalità wedging	± 0,5 %	± 0,5 %
	planarità flatness	± 0,5 %	+ 0,5 % - 0,3 %
ISO 10545/3	assorbimento d'acqua water absorption	E > 10 %	16 %
ISO 10545/13	resistenza agli attacchi chimici chemical resistance	≥ B	≥ B
ASTM C650	chemical resistance		unaffected
ISO 10545/14	resistenza alle macchie stain resistance	≥ CLASSE 3	5
ASTM C1378	stain resistance		≥ B
ISO 10545/11	resistenza al cavillo crazing resistance	resiste resists	resiste resists

LISTINO - PRICE LIST

PREZZO MQ. - SQM. PRICE

NR.	EURO	FRANCO FABBRICA IVA ESCLUSA EX FACTORY EXCLUDING VAT
169	61,00	EURO 8,70 PLT NON INCLUSA EURO 8,70 PLT NOT INCLUDED