outrage

PORCELAIN

usage: medium traffic, PEI 4
colour variation: medium variation



colour	*finish*	**30x30**	**30x60**	**60x60**
artic white	matte		■	■
ipanema sand	matte		■	■
taupe	matte		■	■
buckingham green	matte		■	■
niagara	matte		■	■
thickness (mm)		9	9	9
packaging (pieces/box)		11	8	4

special order (allow 6-8 weeks) ■ stock item

mosaics	
square	2.5x2.5
square	5x5 ■
linear	3x10
random	

test	**standard**	**req'd value**	**test result**
dimensions	ISO 10545-2	various	conforms
water absorption	ISO 10545-3	< 0.5%	0.09%
bending strength	ISO 10545-4	>=1300N	1791
bending strenth	ISO 10545-4	>=35N/mm²	43.8N/mm²
abrasion resistance			PEI 4
thermal shock resistance	ISO 10545-9		conforms
frost resistance	ISO 10545-12		conforms
chemical resistance	ISO 10545-13		GA GLB
stain resistance	ISO 10545-14		class 5
slip resistance	ASTM C1028	dry >0.6	dry 0.69
		wet >0.6	wet 0.63

1. When installing rectangular tiles in a staggered, brick layout, do not stagger the long side more than 1/3 of the length of the tile.
2. Joints of at least 2mm are recommended when installing rectified tiles and a minimum of 4mm for unrectified tiles.
3. These samples are for general reference only. Variations in dimension, veining, shade and colour may occur. Please do not remove samples from board. If full-size or loose samples are required, or to check stock quantity, exact size or thickness contact Stone Tile or your sales rep.
4. Sizes noted are nominal and metric.
5. Special Order items may require a minimum order quantity.

TRENDY TILES
LONDON

www.stone-tile.com

vancouver	604-731-9948
calgary	403-234-7274
toronto	416-515-9000
montreal	514-903-9026
new york	866-669-1103