Roku

EN

Revised September 2026

General information

Construction & performance

Installation guidelines

Environmental & certifications

General information

Current product availability — Roku is offered in a changing assortment of colours, grades, formats and constructions. For current options and product-specific specifications, see the Roku collection page at stone-tile.com or contact your Stone Tile representative.

Collection	Roku
Material	Engineered Hardwood
Species	Varies by colour and configuration; current assortment includes American White Oak, European White Oak, and American Walnut
Colours	American Black Walnut, Iki, Shibui, Kanto, Ima, Komugi, Koromo
Texture	Brushed
Finish	Bona® UV cured — matte sheen
Warranty	Limited residential and light commercial warranty — contact your Stone Tile representative for terms

Construction & performance

Construction	Engineered — hardwood veneer over a multilayer plywood core
Formats & widths	Wide-plank (commonly 6"–7½"), plus 5" herringbone and chevron
Thickness	3/4" (19 mm)
Profile	Tongue & Groove
Bevel	Micro-bevel
Wear layer	Varies by product — see the current Roku product page
Grades	Range from cleaner, uniform looks to more character-rich grades with natural knots; grade varies by product
Radiant heat	Suitable over water-based (hydronic) radiant heat

Product-specific specifications — available sizes, widths, wear-layer thicknesses, grades and formats vary by SKU and may change over time. Refer to the current Roku product page or contact your Stone Tile representative.

Installation guidelines

Use	Residential floors — on, above, or below grade
Installation methods	Nail-down (with glue assist), glue-down, or floating, as permitted for the selected format. Suitable over water-based (hydronic) radiant heat.
Subfloor — plywood	Min. 5/8" APA plywood or 3/4" OSB; level, clean, structurally sound; ≤ 12% moisture content
Subfloor — concrete	Test and prepare per the current installation and adhesive instructions; verify moisture by the specified method
Subfloor flatness	1/8" per 8′
Acclimation	48–72 hours at ~22°C (72°F), 40% RH, per product directions
Expansion gap	3/4" around the perimeter; add transitions per the installation instructions
Environment	20–22°C (68–72°F), 40–50% RH year-round
Adhesive	Moisture-cured urethane polymer (no latex / water-based glues)

Note: Installation methods vary depending on design. Contact your Stone Tile consultant for additional information.

Disclaimer: The installation guidelines provided are the manufacturer's recommendations only. Stone Tile is not responsible for the installation of this product. Always consult a qualified installer and follow all applicable building codes.

Environmental & certifications

FloorScore	Certified (SCS-105 v4.2 / CDPH v1.2-2017)
FSC	Available FSC-certified (Chain of Custody) — confirm at time of order
CARB2 / TSCA Title VI	Compliant (composite-wood formaldehyde)
Formaldehyde emissions	Tested to ASTM E1333
TVOC	≤ 0.5 mg/m3 — low-emitting material