

Vivid

EN

General information

Featured products

Technical performance

Installation guidelines

Environmental & certifications

General information

collection	Vivid
material	Glazed Ceramic Wall Tile
production	Dust-pressed, double-fired (bicottura)
body	White
surface	Handmade, Glossy
water absorption	Group BIII — E > 10% (UNE-EN ISO 10545-3)
nominal sizes	10x10 cm (4"x4") · 5x15 cm (2"x6")
colours	Off White, Ivory, Sage, Army Green, Burgundy

Featured products

Colour	Sizes	Finish	Body
Off White	10x10 · 5x15	Handmade Glossy	White
Ivory	10x10 · 5x15	Handmade Glossy	White
Sage	10x10 · 5x15	Handmade Glossy	White
Army Green	10x10 · 5x15	Handmade Glossy	White
Burgundy	10x10 · 5x15	Handmade Glossy	White

All colours are available in both nominal sizes with the same handmade glossy surface and white ceramic body.

Technical performance

PHYSICAL & MECHANICAL (UNE-EN ISO 10545)

dimensional tolerance	± 0.2% length & width (ISO 10545-2)
thickness tolerance	± 5.6% (ISO 10545-2)
surface quality	99% of tiles free from visible defects
water absorption	Group BIII, E > 10% (ISO 10545-3)
breaking load	345 N (ISO 10545-4)
modulus of rupture	14 N/mm ² (ISO 10545-4)
breaking strength	638 N
scratch hardness (Mohs)	Class 3 (EN 101:1991)
stain resistance	Class 5 (ISO 10545-14)

CRAZING & CHEMICAL RESISTANCE — VARIES BY COLOUR

crazing resistance	Resistant — Off White, Ivory Not resistant / crazes — Sage, Army Green, Burgundy (ISO 10545-11)
acids & alkalis (low)	GLA no visible effect — Off White, Ivory GLB visible effect — Sage, Army Green, Burgundy (ISO 10545-13)
acids & alkalis (high)	GHA no visible effect — Off White, Ivory GHB visible effect — Sage, Army Green, Burgundy (ISO 10545-13)

DCOF / slip and frost resistance are not applicable to this interior wall product and are not reported by the manufacturer.

Installation guidelines

use	Interior walls
installation method	Thin-set / suitable wall-rated tile adhesive, over a sound, clean, flat substrate
layout	Confirm joint width and layout before setting
handmade variation	Natural variation in size, tone, and surface is expected
sealing	Crazing glazes (Burgundy, Army Green, Sage) must be sealed before grouting — see the Vivid Care & Sealing guide

Note: Installation methods vary depending on design. Contact your Stone Tile consultant for additional information.

Disclaimer: The installation guidelines provided are the manufacturer's recommendations only. Stone Tile is not responsible for the installation of this product. Always consult a qualified installer and follow all applicable building codes.

Environmental & certifications

Environmental and health-product documentation (EPD, HPD, SDS, LEED) is not applicable for this collection.