

PUZZLE / technical features

UNI EN14411:2012 App. GL. (Bla Group)

norma standard	caratteristiche features	valore prescritto value required	PUZZLE
ISO 10545/3	assorbimento d'acqua water absorption	<0,5%	0,06%
ASTM C373		<0,5%	0,06%
EN 101	durezza superficiale (scala mohs) surface hardness (scala mohs)	> 5	conforme unaffected
ISO 10545/9	resistenza agli sbalzi termici resistance to thermal shock	nessuna alterazione visibile no visible alteration	resiste resistant
ISO 10545/12	resistenza al gelo frost resistance	nessuna alterazione visibile no visible alteration	resiste resistant
ASTM C1026		unaffected	unaffected
ISO 10545/13	resistenza agli attacchi chimici resistance to chemical attacks	nessuna alterazione visibile no visible alteration	resiste resistant
ASTM C650			unaffected
ISO 10545/4	sforzo di rottura (N) breaking strength (N)	Sp \geq 7,5 min 1300	5019
	Classificazione carico di rottura breaking strenght classification		U4 (carichi pesanti) U4 (heavy weights)
DIN 51130 - 04		valori medi 6° ÷ 10° 10° ÷ 19° 19° ÷ 27° 27° ÷ 35° > 35°	R9 R10 R11 R12 R13 R10
ISO 10545/14	resistenza alle macchie stains resistance	CLASSE 3 MIN. MINIMUM 3	resiste resistant
LEED CERTIFICATION			> 20% PRE-CONSUMER

PUZZLE / packing

formato size	pz-mq pcs-sqm	pz-scat. pcs-box	mq-scat. sqm-box	scat-pal. box-pal.	kg-scat. kg-box	kg-pal. kg-pal.	mq-pal sqms-pal
25-25	16	12	0,75	60	22,20	1332,00	45,00
set of 6 patterns 25-25	16	12	0,75	60	22,20	1332,00	45,00
edge 25-25	16	12	0,75	60	22,20	1332,00	45,00
battiscopa 12,5-25	-	10	2,5 ml	-	9,25	-	-



V1
variazione uniforme
uniform variation